



Option 1:
Non-approved Version (EHI-CW)

Option 2:
OIML Approved Version (EHI-E1)



Features

- **Applications:** Livestock, pets, feed carts, bulk containers, shipping and receiving
- **Loadcell:** EH-AMC-S/M: Four-point aluminum loadcells, resolution up to 1/3,000
EH-AMC-L: Four-point ZEMIC H8C aluminum loadcells, resolution up to 1/3000
- **Construction:** Heavy-duty mild steel understructure with checkered plate surface and 2 built-in ramps
Low profile in 2.5" (64mm) high protects animals and handlers from slips and falls
Level bubble and adjustable feet ensure quick set-up and stability
IP65 waterproof junction box with top access for easy installation and service
Optional indicator stand for waist-level reading
- **Indicator:** EHI-CW: Rugged ABS plastic enclosure with LED display
EHI-E1: Aluminum alloy housing with FSTN backlit LCD display
- **Functions:** EHI-CW: Weighing, Tare, Hold, Print and Auto-off function
EHI-E1: Weighing, Check-weighing, Tare, Counting, Hold, Accumulation, Percentage
GEO calibration, optional Bluetooth function

Specifications


Item	Parameters		
Model	EH-AMC-500	EH-AMC-1000	EH-AMC-1500
Capacity	500kgx0.2kg / 1000lbx0.5lb	1000kgx0.5kg / 2000lbx1lb	1500kgx0.5kg / 3000lbx1lb
Platform Size	510x1400mm / 20"x55"	762x1497mm / 30"x59"	1000x2000mm / 39.4"x78.8"
Packing Size	1540x650x170mm/1pc/ctn	1620x910x170mm/1pc/ctn	2050x1050x1260mm/7pcs/plt
Shipping Weight	G.W.: 35kg N.W.: 33.5kg	G.W.: 48kg N.W.: 46kg	G.W.: 990kg N.W.: 980kg
Units of Measure	EHI-CW: kg, lb; EHI-E1: kg, lb, oz, pcs, %		
Display	EHI-CW: 6 digits, 0.8" (20mm) high, 7 segments LED display EHI-E1: 6 ½ digits, 1" (25mm) high, 7 segments FSTN backlit LCD display		
Power	EHI-CW: 12V 500mA adapter or 6V 4Ah lead-acid rechargeable battery EHI-E1: 9V 600mA adapter or 4xAA battery		
Serial Port	EHI-CW: RS232; EHI-E1: USB & RS232		
Operation Temp	-10°C to 40°C (14°F to 104°F)		
Approvals	CE and WEEE directive, UL/CE/BS/VI Energy approved power adapter		
Options	Indicator stand, RS232 cable, USB cable, wheels		

Dimensions (mm/inch)


	L	W	H
EH-AMC-1000	510/20"	1400/55"	64/2.5"
EH-AMC-1000	762/30"	1497/59"	64/2.5"
EH-AMC-1000	1000/39.4"	2000/78.8"	88/3.5"



- Non-approved: with EHI-CW indicator and non-approved loadcells
- OIML & EC Type approved: with OIML EHI-E1 indicator & OIML loadcells
OIML Cert. No.: R76/2006-NL1-16.09;
EC Type Cert. No.: T8557



- Low profile platform with built-in ramps for easy entry
- Various sizes of platforms for selection
- Four point aluminum loadcells, resolution up to 1/3,000



- 4 adjustable foot pads for quick stability
- With handles for easy movement
- With IP65 waterproof junction box for easy maintenance