

Option 1:
Non-approved version (EHI-B)




Option 2:
Approved version (EHI-E1)



- Non-approved: with EHI-B indicator and non-approved loadcells
- OIML & EC Type approved: with OIML EHI-E1 indicator and OIML loadcells
OIML Cert. No.: R76/2006-NL1-16.09;
EC Type Cert. No.: T8557



- Low profile platform with heavy-duty welded structure for easy entry
- Various sizes of platforms for selection
- 4 point aluminum loadcells, resolution up to 1/3,000



- IP65 waterproof junction box for easy maintenance
- 4 adjustable feet for quick stability

Features

- **Applications:** Legal-for-trade application:
Livestock, pets, feed carts, bulk containers, shipping and receiving
- **Loadcell:** Four-point alum. load cells construction, resolution up to 1/3000
- **Construction:** Durable heavy-duty mild steel understructure
Removable brushed stainless steel platform for easy cleaning
Extreme low profile 2.5" (64mm) high platform provides more safety
Adjustable feet allow scale to work effectively on uneven floors
IP65 waterproof junction box for easy service for 550x500mm and 550x900mm platforms
Optional indicator stand for waist-level reading
- **Indicator:** EHI-B: Rugged stainless steel housing with FSTN backlit LCD display
EHI-E1: Aluminum alloy housing with FSTN backlit LCD display
- **Functions:** EHI-B: Weighing, Tare, Hold and Auto-off
EHI-E1: Weighing, Hold, Tare, Preset Tare, and Auto-off

Specifications

Item	Parameters			
Model Number	EH-AMS-S	EH-AMS-M	EH-AMS-L	EH-AMS-T
Capacity	60kg~150kg	60kg~300kg	150kg~500kg	150kg~500kg
Platform Size	366x366mm / 15"x15"	400x500mm / 16"x20"	550x550mm / 22"x22"	550x900mm / 22"x36"
Packing Size	550x490x400mm/4pcs/ctn	640x530x250mm/2pcs/ctn	710x710x290mm/2pcs/ctn	1040x690x145mm/1pc/ctn
Shipping Weight	G.W.: 30kg N.W.: 26kg	G.W.: 20kg N.W.: 18kg	G.W.: 29kg N.W.: 26kg	G.W.: 21.5kg N.W.: 20kg
Units of Measure	kg, lb, lb:oz			
Display	EHI-B: 5 ½ digits 0.625" (16mm) high, 7 segments backlit LCD display EHI-E1: 6 ½ digits 1" (25mm) high, 7 segments backlit LCD display			
Power	DC 9V 600mA power adapter; 4xAAA batteries			
Serial Port	EHI-B: RS232; EHI-E1: RS232 & USB			
Operation Temp	-10°C to 40°C (14°F to 104°F)			
Approvals	CE and WEEE directive, UL/CE/BS/VI Energy approved power adapter			
Options	Indicator stand, RS232 cable, USB cable, Remote display			

Dimensions (mm/inch)

	EH-AMS-S	EH-AMS-M	EH-AMS-L	EH-AMS-L
L	366/14.4"	500/19.7"	550/22"	900/36"
W	366/14.4"	400/15.8"	550/22"	550/22"
H	44.7/1.8"	64.2/2.5"	66.2/2.6"	74.2/2.8"
A	260/10.2"	383/15.1"	421.5/16.6"	750.5/29.5"
B	262/10.3"	285/11.2"	421.5/16.6"	401.5/15.8"
C	23.2/0.9"	23.2/0.9"	32/1.3"	32/1.3"

