



EH-SU with plastic housing

EH-SS with stainless steel housing



- IP68 waterproof design, allows to use in high humidity and harsh environment



- Front LED display with 4 keys operation for operator's view
- An optional rear LED display is available for customer's view



- Built-in IP68 waterproof AC adapter and rechargeable battery

Features

- Applications:** Portion control, food processing, meat preparations areas, catering kitchens etc.
- Loadcell:** IP68 & anti-corrosion aluminum loadcell makes system resolution up to 1/7,500
- Construction:** IP68 waterproof class
EH-SU: ABS washdown housing with stainless steel platter
EH-SS: Stainless steel washdown housing with stainless steel platter
Levelling bubble and adjustable foot ensure the quick set-up and stability
Integrated carry handles for easy portability
Available calibration switch allows fast access to calibrate the scale
- Indicator:** LED display (single or dual) with adjustable LED brightness level
Simple-to-operate keyboard-off, on/zero, push button tare and set
Annunciators: kg, g, lb, oz, tare, over, under, accept, count, zero, and battery voltage
- Functions:** Weighing, Check-weighing, Counting and Auto power saving

Specifications

Item	Parameters			
Model	EH-SS/SU-3	EH-SS/SU-6	EH-SS/SU-15	EH-SS/SU-30
Capacity	3kgx0.5g 6lbx0.001lb	6kgx1g 15lbx0.002lb	15kgx2g 30lbx0.005lb	30kgx5g 60lbx0.01lb
Units of Measure	kg, g, lb, lb:oz			
Display	Sealed watertight 7 segments, 6 digits, 13mm(0.5") high red LED display with annunciators			
Function Keys	ON/ZERO, OFF, SET(0~9), TARE			
Power	Internally mounted AC adapter or 6V 4Ah lead-acid rechargeable battery			
Operation Temp	-10°C to 40°C (14°F to 104°F)			
Platter	224mm(L)x186mm(W) / 8.82"(L)x7.31"(W)			
Packing	590x350x300mm/4pcs/ctn			
Shipping Weight	G.W.: 18kg N.W.: 15kg			
Approvals	CE and WEEE directive, UL/CE/BS approved power adapter			
Options	Single display; Dual display			

Dimensions (mm/inch)

