




- **FSTN LCD display with backlit**, clear to see from any angle of view
- 3 keys for easy operation



- Table and wall mounted brackets
- Optional pole stand



- Bi-directional RS232 interface, allows to communicate with computers

Features

- **Applications:** Widely used on shipping scales, physician scales, livestock scales, platform scales and any general weighing purpose
- **Construction:** Stainless steel housing/ABS case, complete with wall bracket and desk mount
- **Display:** 5 ½ digits 0.625" (16mm) high, 7 segments backlit FSTN LCD display and annunciators: zero, net, hold, lb/kg
- **Keys:** ZERO/ON/OFF, UNIT/HOLD, TARE
- **Protocol:** Standard NCI interface to most common shipping software incl. UPS worldship online and Fedex
- **Functions:** Weighing, BMI, Hold, Auto-off time setting

Specifications

Item	Parameters
Loadcell Capability	4 @ 350ohm
Excitation voltage	5V DC
Wiring	4 wires, 20cm pigtail cable
Units of Measure	kg, lb, lb:oz
Serial Port	RS232
Power	9V 600mA adapter or 4xAA batteries
Operation Temp	0°C to 40°C (32°F to 104°F)
Packing size	57x47x56cm/20pcs G.W.: 26kg N.W.: 24kg
Approvals	CE and WEEE directive, UL/CE/BS/VI Energy approved power adapter
Options	RS232 cable, desk bracket, indicator stand

Dimensions (mm/inch)

