



EHW-EM
with LED display



EHW-CM
with LCD display



- EHC-EM: Red LED display with 3 levels of brightness
EHC-CM: FSTN LCD display with backlit, clear to see from any angle of view



- Aluminum loadcell support, safety for food weighing
- Removable stainless steel platter for easy clean-up



- EHW-EM: 6V 4Ah rechargeable battery or AC adapter
EHW-CM: 4xAA batteries or AC adapter

Features

- **Applications:** Warehouse, shops, Stores, or other industrial and commercial weighing
- **Load cell:** Single point Alum. load cell makes system resolution up to 1/7,500
- **Construction:** ABS plastic housing with aluminum loadcell support
Removable stainless steel platter for convenient cleaning
Optional wipedown dust cover to protect scale from dust and food particles
Leveling bubble and adjustable feet for quick set-up and stability
- **Indicator:** EHW-EM: Easy-to-read LED display with 3 levels of brightness
EHW-CM: FSTN LCD display with backlit, clear to see in any angle of view
2 keys: ON/OFF/ZERO, TARE/UNITS
- **Functions:** Weighing, One-step successive Tare feature

Specifications

Item	Parameters			
Model	EHW-EM/CM-3	EHW-EM/CM-6	EHW-EM/CM-15	EHW-CM-20
Capacity	3kgx0.5g	6kgx1g	15kgx2g	20kgx10g
	6lbx0.001lb	12lbx0.002lb	30lbx0.005lb	40lbx0.01lb
Units of Measure	kg, lb, g, oz, lb:oz			
Display	EHW-EM: 7 digits 0.7"(17mm) high, 7 segments LED display			
	EHW-CM: 5 1/2 digits 0.65" high LCD display with backlit			
Power	EHW-EM: 12VDC 500mA adapter or 6V 4Ah lead-acid rechargeable battery EHW-CM: 9VDC 600mA adaptor or 4xAA batteries			
Operation Temp	-10°C to 40°C (14°F to 104°F)			
Platform Size	245mm(L)x215mm(W) 9.65"(L)x8.46"(W)			
Packing	680x400x630mm/6pcs/ctn			
Shipping Weight	G.W.:26kg N.W.:24kg			
Approvals	CE and WEEE directive, UL/CE/BS/VI Energy approved power adapter			

Dimensions (mm/inch)

